

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1. (previously presented) A method of detecting application spoofing in a mixed use avionics display by indicating when the mixed use avionics display is displaying information from a non-certified source, the method comprising the steps of:
 - providing an avionics display having a display area that is capable of displaying information from a non-certified source;
 - displaying a certified display on the display area;
 - providing a data connection between the avionics display and the non-certified source;
 - providing information from the non-certified source to the avionics display;
 - displaying the information on the display area so that less than the entire display area displays the information;
 - maintaining the displaying of the certified display on the display area while simultaneously displaying the information from the non-certified source;
 - displaying the information on the display area in front of the certified display so that the information is visible on the avionics display, at least a portion of the certified display is visible on the avionics display and the information covers a portion of the certified display that would otherwise be displayed; and

indicating to a user that application spoofing is possible by partitioning the display area so that at least a portion of the display area cannot display the information from the non-certified source.

2. (cancelled)

3. (previously presented) The method of claim 1, wherein the step of partitioning the display area further comprises the step of:

providing the non-certified source with a false indication of the size of the display area so that the non-certified source is not capable of addressing the entire display area.

4. (original) The method of claim 3, wherein the step of providing the non-certified source with a false indication of size further comprises the step of:

providing the non-certified source with a false display address so that the non-certified source is not capable of addressing the entire display area.

5. (original) The method of claim 3, wherein the step of providing the non-certified source with a false indication of size further comprises the step of:

providing a false horizontal display size so that the non-certified source is not capable of addressing the entire display area.

6. (original) The method of claim 3, wherein the step of providing the non-certified source with a false indication of size further comprises the step of:

providing a false vertical display size so that the non-certified source is not capable of addressing the entire display area.

7. (previously presented) The method of claim 1, wherein the avionics display is comprised of a visual display monitor and a computer processor and the step of partitioning the display area further comprises the step of:

the computer processor limiting the display area in which the information can be displayed.

8. (cancelled)

9. (original) The method of claim 1, further comprising the steps of:

displaying a visual indicator on the display area whenever the information is being displayed; and

preventing the displaying of the information from blocking the visual indicator so that the visual indicator is always visible on the display area when the information is being displayed.

10. (original) The method of claim 9, wherein the step of preventing the displaying of the information from blocking the visual indicator further comprises the step of:

displaying the visual indicator on a portion of the display area that is not used to display the information so that the visual indicator is always visible when displaying the information.

11. (previously presented) The method of claim 9, wherein the step of preventing the displaying of the information from blocking the visual indicator further comprises:

displaying the visual indicator on a portion of the display area that is used to display the information; and

superimposing the visual indicator in front of the information being displayed so that the visual indicator is always visible when displaying the information regardless of a location within the display area in which the information is being displayed.

12.-16. (cancelled)

17. (previously presented) A method of allowing an aircraft certified flight deck display to be used as a mixed use avionics display by indicating when the certified flight deck display is displaying information from a non-certified source, the method comprising the steps of:

providing an aircraft having a certified flight deck display;

providing a data connection between the certified flight deck display and a non-certified source of information;

providing information from the non-certified source to the certified flight deck display;

limiting space on the certified flight deck display in which the information can be displayed so that an entire display area cannot be used to display the information by partitioning the display area so that at least a portion of the display area cannot display the information from the non-certified source;

providing the non-certified source with a false indication of the size of the display area so that the non-certified source is not capable of addressing the entire display area; and

indicating that a potential for application spoofing exists by displaying the information in the limited space on the certified flight deck display.

18.-19. (cancelled)

20. (original) The method of claim 17, further comprising the steps of:
displaying a certified display on the display area;
displaying the information from the non-certified source on the display area in front of the certified display; and
maintaining the displaying of the certified display on the display area while simultaneously displaying the information from the non-certified source so that the information is visible on the certified flight deck display and at least a portion of the certified display is visible on the certified flight deck display.

21. (original) The method of claim 17, further comprising the steps of:
placing a visual indicator on the display area whenever the information is being displayed; and
preventing the displaying of the information from blocking the visual indicator so that the visual indicator is always visible on the display area when the information is being displayed.

22. (cancelled)